

PORTABLE ELECTRONIC APPARATUS, IMAGE
PROCESSING METHOD, PHOTOGRAPHING APPARATUS,
AND COMPUTER READABLE RECORDING MEDIUM

5 BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates to a portable electronic
apparatus such as a digital camera or the like, an
image processing method and a photographing apparatus
10 which are used for such an apparatus, and a computer
readable recording medium which is used for such method
and apparatus.

Related Background Art

In recent years, digital cameras have
15 progressively been spread owing to the advancement of a
semiconductor technique and the like. However, since a
price of an image memory, particularly, a semiconductor
memory which can be used in the digital camera is
expensive, the number of images which can be
20 photographed by using the image memory which is
equipped as a standard memory in the camera is not so
enough as compared with a general photographing
frequency that is required for the camera. Therefore,
a product such that an exchangeable device, for
25 example, a flash memory card or smart memory of PCMCIA
is used as an image memory and this image memory is
exchanged in accordance with the necessity of the user,

006240" 6 T 69060

and the number of images which can be photographed is increased also exists.

However, it is fairly difficult to obtain the flash memory card or smart memory as compared with the silver salt film and they cannot be always obtained as necessary. When photographing, therefore, the user has to carry an enough large amount of flash memory card or the like for the presumed number of photographing images. Such a situation cannot be said that the feature that an erasable memory device is used as an image memory is effectively used.

If a magnetic memory such as a hard disk or the like is used as an image memory instead of the semiconductor memory, an enough large number of photographing images can be assured as compared with the general photographing frequency that is required for the camera. However, in case of using the magnetic memory, a necessary electric power consumption is large and an external shape of the camera enlarges as compared with that in case of using the semiconductor memory, so that the magnetic memory is improper as a memory device of the digital camera.

As mentioned above, in the present digital camera, since the number of images which can be photographed is limited depending on the degree of obtaining the exchangeable device or the capacity of the built-in image memory, if the user has to photograph images of

09069419 042998
856270 57469060

the number which exceeds the limited number, at the
photographing spot, unnecessary images have to be
erased from the images which have already been
photographed or the user himself must transfer the
5 image memory to the other personal computer or the like
and increase the available image memory. Unless
otherwise, the user cannot photograph.

However, the execution of such a work at the
photographing spot causes a time loss and becomes a
10 large drawback for the camera which requires
instantaneousness. Further, in order to judge the
unnecessary images from the photographed images, it is
necessary to confirm various information. Therefore,
the execution of such a work by the digital camera
15 itself whose processing speed is relatively slower than
that of the personal computer becomes a large burden
for the photographer.

Particularly, in a small display equipped for the
digital camera, it is generally difficult to
20 discriminate whether the photographed images are good
or not. To efficiently perform such a work, a new key
switch group, a display to confirm the information, and
the like which are not used in the ordinary digital
camera are necessary. They obstruct the realization of
25 miniaturization of the digital camera.

Moreover, a resistance feeling against the work to
erase the photographed images at the photographing spot

0906949-04299
866240-57469060

is strong for the photographer. Although there is not such a burden in case of transferring to the other memory device of a personal computer or the like, the user has to carry an interface or the like between the
5 personal computer and the digital camera, it is troublesome, and a physical burden increases.

SUMMARY OF THE INVENTION

It is an object of the invention to solve each or
10 all of the above problems.

Another object of the invention is to enable images to be fetched even when an image memory is insufficient.

Still another object of the invention is to
15 provide a portable electronic apparatus, an image processing method, a photographing apparatus, and a computer readable recording medium of a digital camera or the like, in which even if an image memory is likely to be insufficient, the image memory can be further
20 used while assuring the stored images.

Under the above objects, according to a preferred embodiment of the invention, there is disclosed a portable electronic apparatus comprising: image pickup means for photographing an object and outputting an
25 image signal; image memory means for storing the image signal; and communicating means for automatically transmitting the image signal stored in the image

0065419 042998
866240 6769060

There is also disclosed an image processing method comprising the steps of: storing a photographed image signal into image memory means; and automatically transmitting the image signal stored in the image memory means so as to enable a new image signal to be stored in the image memory means.

There is also provided a photographing apparatus comprising: image pickup means for photographing an object and outputting an image signal; image memory means for storing the image signal; remaining amount detecting means for detecting a remaining amount of the image memory means; discriminating means for discriminating whether the photographing by the image pickup means can be performed or not on the basis of the detected remaining amount; image selecting means for selecting an image signal from the image memory means on the basis of a predetermined selecting

condition when a discrimination result indicates the photographing is impossible; and communicating means for transmitting the selected image signal.

Further another object of the invention is to
5 enable a wireless image communicating function to be effectively used.

Further another object of the invention is to provide a portable electronic apparatus and a photographing apparatus in which usability is improved.

10 Still another object of the invention is to provide a cellular phone and a photographing apparatus having a new function.

The above and other objects and features of the present invention will become apparent from the
15 following detailed description and the appended claims with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing an embodiment of
20 a digital camera to which the invention is applied;

Figs. 2A, 2B, 2C and 2D are external perspective views of the digital camera according to the first embodiment of the invention;

Fig. 3 is a block diagram showing the first
25 embodiment of the invention;

Fig. 4 is a flowchart showing a whole control of the first embodiment of the invention;

09069419.042998

Fig. 5 is a flowchart showing a control to assure an image memory in the first embodiment of the invention;

Fig. 6 is a flowchart showing a control method of an image selecting unit in the first embodiment of the invention;

Fig. 7 is a flowchart showing another control method of the image selecting unit in the first embodiment of the invention;

Fig. 8 is a flowchart showing a whole control of the second embodiment of the invention;

Fig. 9 is a block diagram showing the third embodiment of the invention;

Fig. 10 is a block diagram of an image processing apparatus according to the third embodiment of the invention;

Fig. 11 is a block diagram showing an image processing apparatus according to the fourth embodiment of the invention; and

Fig. 12 is a block diagram showing an image processing apparatus according to the fifth embodiment of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 is a block diagram showing a construction of a digital camera to which the invention is applied.

In Fig. 1, reference numeral 101 denotes a lens

0065419 67469060

using a triple manual zooming system in the embodiment.
A low pass filter of an optical system is equipped to
reduce a color moire.

Reference numeral 102 denotes a color CCD image
5 sensor (hereinafter, simply referred to as a CCD) of,
for example, a full pixel reading system of 330,000
square pixels of 1/4 inch. The light converged by the
lens 101 is formed as light on the surface of the CCD
102 and is converted into an electric signal.

Reference numeral 103 denotes a CCD control unit
10 for generating a timing signal for the CCD 102,
sampling and holding of image data outputted from the
CCD 102, an A/D conversion, a color space conversion of
YUV → RGB, and a gain control and also controls a flash
15 104 and an AF/AE/AWB operating unit 105.

Reference numeral 104 denotes the built-in flash
which is charged or which emits light by an instruction
from the CCD control unit 103 at night or the like.

Reference numeral 105 denotes the operating unit
20 of AF (auto-focusing), AE (auto-exposure), and AWB
(auto white balance).

Reference numeral 106 denotes a TFT color display
of 2 inches made of low temperature polysilicon. The
display 106 is connected to a video LCD controller 110
25 by an NTSC interface. The color display 106 displays a
color image as a view finder and a color image recorded
in the image memory and displays a color image

09069419 042998

transmitted by communication.

Reference numeral 107 denotes a black and white STN liquid crystal display of (320 × 240) dots. A touch panel 121 is attached onto the display surface of the display 107. The display 107 displays characters and also displays a button, a window, and the like for the inputting operation from the user by using the touch panel 121 and is connected to a graphic LCD controller 111 by a digital interface.

Reference numeral 108 denotes a memory group comprising a flash memory of 4 MB which is used as an image memory, which will be explained hereinlater, a DRAM of 4 MB to execute a built-in OS and a program, and a mask ROM of 6 MB to store the program.

Reference numeral 109 denotes a compact flash card. The card 109 is a separating type semiconductor memory which is used as an auxiliary storage of the image memory. The flash card 109 is connected to a PCMCIA controller 113 by a PCMCIAATA interface.

Reference numeral 110 denotes a video LCD controller having a frame memory for an NTSC picture plane. The controller 110 has a scan converter function for performing a conversion of resolution and an absorption of a timing in order to display RGB image data which is transmitted from the image memory provided in the CCD control unit 103 or memory group 108 onto the NTSC TFT display.

0006949-042998

Reference numeral 111 denotes a graphic LCD controller having a video memory for a graphic picture plane. The controller 111 is used for display of a text, GUI, or the like and is used to display data stored in a DRAM, mask ROM, or the like in the memory group 108.

Reference numeral 112 denotes a memory controller for generating a timing signal and a signal for various memories of the memory group 108.

Reference numeral 113 denotes the PCMCIA controller which is connected to a built-in type RISC CPU which is used in the digital camera and serves as an interface to a compact flash card 109.

Reference numeral 114 denotes a resolution converting unit for converting resolution by performing a temporary storage and a sampling of the image data which is transmitted by the CCD control unit 103. For example, upon framing of the digital camera, since there is no need to process all of the data, the image of (640 × 480) dots which is outputted from the CCD control unit 103 is thinned out and converted into the image of (160 × 120) dots by the resolution converting unit 114 and is transferred to the video LCD controller 110. Upon normal photographing, the image data is temporarily stored into a buffer as an image of (640 × 480) dots as it is and, after that, the image data is transferred to an image compression/expansion unit 115

09069419.042998
856240" 6769060

Reference numeral 115 denotes the image compression/expansion unit for compressing and expanding the image. In the embodiment, hardware for performing compression and expansion of JPEG or Wavelet is installed. Such a compression and expansion system is not limited by the embodiment but other various methods can be applied. After the data formed as an image onto the CCD 102 was signal processed by the CCD control unit 103, for example, the JPEG image compression is performed by the image compression/expansion unit 115 and is compressed to about 1/15 of the original image. Since the quantization table and the Huffman coding table have rewritable structures, by rewriting the contents in the table 3, a compression ratio can be changed. Although the ordinary digital camera has a function for making a file size per image constant and making the management of the number of images which can be photographed easy, in the embodiment, this function is embodied by performing the compression a plurality of times. That is, when a data size is larger than the set file size, the coding table is changed so as to increase the compression ratio. When it is smaller than the set file size, the coding table is changed so as to reduce the compression ratio.

Reference numeral 116 denotes an infrared standard

interface (IrDA) including a light emitting unit and a photosensing unit. The interface 116 is used when exchanging data with other notebook computers or the like.

5 Reference numeral 117 denotes a built-in type RISC microprocessor (CPU) for performing various controls of the digital camera.

 Reference numeral 118 denotes an audio compression/expansion unit for compressing and
10 expanding an audio signal. The audio compression/expansion unit 118 compresses the digital audio data transmitted from a microphone 119a provided in an audio input/output unit 119 and an A/D converter by a method such as ADPCM, GSM, or the like and
15 transfers the compressed data to the CPU 117. After the digital audio data arrived from the CPU 117 was D/A converted by the audio input/output unit 119, the converted analog signal is generated as a sound from a speaker 119b.

20 Reference numeral 121 denotes an analog touch panel of the resistance dividing type installed on the black and white display 107. Various data, instructions, and the like are inputted by the touch panel 121. The data outputted by the touch panel 121
25 is converted into digital data by an A/D converter 120 and is transmitted to the CPU 117.

 Reference numeral 122 denotes a PHS communication

0905949-042998
866240-67469060

unit for communicating various data which is communicated with the CPU 117 to a PHS base station by PIAFS and ARIBSTD28 protocol.

Reference numeral 123 denotes an antenna of the PHS communication unit 122.

Reference numeral 124 denotes a switch group such as shutter button, marking button, and the like for inputting instructions from the user. Particularly, a half-pressing state and a full-pressing state of the shutter switch (button) are detected. Detection signals are supplied to a sub CPU 125, through which they are transmitted to the CPU 117.

The sub CPU 125 has a function for saving an electric power consumption of the whole system by performing a power management including a battery 126.

Figs. 2A to 2D are external views of a digital camera according to the embodiment.

The digital camera is mechanically largely divided into a block shown at 201 in which an antenna, lenses, and the like are enclosed and a block shown at 202 in which a color display and a microphone are enclosed.

In the block 201, the lens 101, antenna 123, IrDA interface 116, battery 126, speaker 119b, switch group 124, black and white display 107, and touch panel 121 shown in Fig. 1 are provided. Reference numeral 203 denotes a shutter switch (button) provided for the switch group 124 in Fig. 1.

09069419 042998

In the block 202, the microphone 119a and color display 106 shown in Fig. 1 are provided.

As shown in Fig. 2A, the blocks 201 and 202 are connected by an axis 204 and can be rotated by 360° around the axis 204 as a center as shown by an arrow A. As shown in Figs. 2A and 2B, consequently, upon photographing as an ordinary camera, the user can photograph an object while looking at the object via the color display 106, so that an operating feeling without a sense of physical disorder as a camera is obtained (status A). By rotating the block 202 as shown in Figs. 2C and 2D, the user can photograph the object while observing a self object image (status B). In the status B, since the microphone 119a and speaker 119b are located on the same plane, the apparatus can be used as a cellular phone and its operating feeling is extremely natural. On the other hand, in the status A, since the microphone 119a is directed toward the object and the speaker 119b is directed toward the photographer, the apparatus can be naturally operated as a movie camera to photograph a moving image.

Fig. 3 is a block diagram showing the first embodiment of the invention extracted from the construction of Fig. 1.

In Fig. 3, reference numeral 301 denotes an image input unit including image pickup means. The image input unit 301 executes a signal process of the image

09069419 042998
366240 67469060

inputted by the lens 101 and is constructed while including each unit of 101, 102, 103, 114, 117, and 112 in Fig. 1.

Reference numeral 302 denotes an image memory. A
5 flash memory in the memory group 108 in Fig. 1 is used.

Reference numeral 303 denotes a memory managing table constructed in the flash memory. An example of items of the contents stored in this table and the contents of a table stored there is shown in Table 1.

10

09030419 1042998
866240 67463060

Table 1

Name	Size	Recording date/time	Accessing date/time	The number of accessing times	Marking	The number of colors used	Recording location
MX0001.jpg	25KB	1996/12/25 PM3:00	1997/1/7 PM10:00	3	x	32768	100
MX0002.jpg	50KB	1996/12/31 AM9:45	1996/12/31 AM9:45	1	o	66536	125
MX0003.jpg	100KB	1997/1/3 PM2:10	1997/1/5 AM3:00	1	x	37	175
MX0004.jpg	50KB	1997/1/7 AM10:30	1997/1/7 PM9:30	7	x	65536	275

In Table 1, there are four JPEG images of MX0001.jpg to MX0004.jpg and information of a size, a recording date/time, an accessing date/time, the number of accessing times, marking information, the number of colors used, and a recording location of each image has been recorded. The above information is used in a transmission image selecting algorithm, which will be explained hereinlater.

In Fig. 3, reference numeral 304 denotes an image selecting unit. When the recording is OK on the basis of a discrimination signal which is sent from an image record discriminating unit 306, the image selecting unit 304 executes nothing. However, when the recording is NG, the image selecting unit 304 selects a proper image from the memory managing table 303 by an algorithm, which will be explained hereinlater, and transfers the selected image to a data transmitting device 305. In Fig. 1, this means that the CPU 117 executes processes in accordance with a program stored in an ROM in the memory group 108 and the image is transferred from the flash memory in the memory group 108 to the PHS communication unit 122.

Reference numeral 305 denotes the data transmitting device and PHSPIAFS is used as a transmitting system in the embodiment. The data transmitting device is constructed by including the PHS communication unit 122 and antenna 123 in Fig. 1.

09069419.042998
866240.6769060

Reference numeral 306 denotes the image record discriminating unit for comparing a remaining amount of the image memory 302 which is sent from a remaining amount calculating unit 308 with an image size written in an image size table 307, thereby judging whether the remaining photographing operation can be performed or not. In this judgment, information in the image size table 307, namely, information indicating to which size the image mode selected at present corresponds is used as a reference of discrimination.

Reference numeral 307 denotes the image size table and its contents are shown in Table 2. The table 307 is stored in the ROM in the memory group 108 in Fig. 1.

TABLE 2

Recording image mode	Memory size necessary per image memory
Economy	25 kB
Normal	50 kB
Fine	100 kb

In Table 2, there are Economy, Normal, and Fine as recording image modes. Memory sizes which are necessary for recording in those modes are set to 25 kB, 50 kB, and 100 kB per image, respectively.

Reference numeral 308 denotes the remaining amount

calculating unit for calculating a remaining amount of a flash memory serving as an image memory 302 of the memory group 108 by the CPU 117.

Fig. 4 is a flowchart showing a whole control of the embodiment.

In step S401, a power source is turned on and the processing routine is started.

In step S402, an initial setting of various devices and circuits is performed.

In step S403, a check is made to see if the photograph mode has been changed. For example, a check is made to see if the photograph mode of Economy, Normal, or Fine mentioned above has been changed from the former mode. If it was changed, since there is a possibility that a necessary capacity of the image memory 302 cannot be reserved, an image memory reserve subroutine is called in step S404. If the photograph mode is not changed, since this means that the image memory 302 has been reserved, the processing routine advances to step S405.

In step S405, a check is made to see if the shutter switch 203 has been fully depressed and turned on. If it is not ON, the control is again shifted to step S403. If it is ON, since this means that the picture was taken, a photographing process is executed in step S406. Since the photographing is finished in step S407, the memory reserve subroutine is called for

09065419 04299B

preparation of a next photographing.

Fig. 5 is a flowchart showing a control for reserving the image memory in steps S404 and S407.

When the processing routine is started in step
5 S501, the remaining amount of the image memory 302 is
detected in step S502 in order to discriminate whether
the recording can be further performed by using the
recording mode selected at present. The image memory
amount used by the image which has already been stored
10 is calculated by using the memory managing table 303 in
Table 1 and the remaining memory amount which can be
used is calculated from the calculated used image
memory amount. The above discrimination about the
recording is made on the basis of the calculated value
15 of the remaining memory amount which can be used, the
recording image mode as contents of the image size
table 307 in Table 2, and the memory size necessary per
image.

If the recording can be further performed, since
20 there is no problem, the processing routine is returned
to the former process in step S506.

If the recording is impossible, a transmission
image selecting subroutine is called in step S503.

In step S504, the image selected in step S503 is
25 transmitted by the data transmitting device 305.

In step S505, the image transmitted in step S504
is erased from the image memory 302, thereby increasing

09069419 042998
B66240 61469050

the remaining amount of the image memory 302, so that a new photographing can be performed. After that, the processing routine is returned to the former process in step S506.

5 Fig. 6 is a flowchart showing a control method in step S503 by the image selecting unit 304.

 When the processing routine is started in step S601, a temporary image is automatically selected by using image management information locating at the head
10 of the memory managing table 303 in Table 1 in step S602. Such a selection can be performed by the user himself or can be automatically executed by the apparatus.

 In step S603, image management information of a
15 next image in the memory managing table 303 in Table 1 is loaded.

 In step S604, whether the loading is successful in step S603 or not is discriminated. If it is unsuccessful, since this means that there is no
20 remaining image, the image which has already been selected is the oldest image.

 If the loading is successful, since this means that there are still images, the control is shifted to step S605.

25 In step S605, the making date/time is extracted from the image management information loaded in step S603 and a check is made to see if the date of the

09069419 1042998

If it is not old, since the image selected at present is the oldest image, next image management information is retrieved from step S603.

Fig. 7 is a flowchart showing another control
10 method of step S503 by the image selecting unit 304.

20 If it is larger, the processing routine is
 returned to step S703 and next image management
 information is retrieved.

As another algorithm for selecting a transmission

5

10

15

20

25

According to the embodiment, the image data is automatically transmitted from the image memory irrespective of the operation of the user and the remaining amount of the memory automatically increases.

5 Therefore, the apparatus can be easily used.

The second embodiment will now be described.

Although a construction of the digital camera in the second embodiment is similar to that of the first embodiment, a whole control method differs from that of
10 the first embodiment. That is, by pressing the shutter switch to about the half position, the operation to reserve the image memory is started.

Fig. 8 shows a flowchart for the whole control according to the second embodiment.

15 When the power source is turned on in step S801, an initial setting of various devices and circuits is executed in step S802.

In step S803, a check is made to see if the photograph mode has been changed. For example, a check
20 is made to see if the photograph mode of Economy, Normal, or Fine has been changed from the former mode. If it was changed, since there is a possibility that a necessary capacity of the image memory cannot be reserved, an image memory reserve subroutine is called
25 in step S804. If the photograph mode is not changed, since this means that the image memory has been reserved, the processing routine advances to step S805.

09069419-042998
866240-67469060

5

10

15

20

25

When the recording is OK by the discrimination signal which is sent from the image record discriminating unit 306, the image selecting unit 304 executes nothing. However, if it is NG, the image selecting unit 304 selects the proper image from the memory managing table 303 by the algorithm mentioned in Figs. 6 and 7 and transfers the selected image to an image processing apparatus 309 by the embodiment. This denotes that, in Fig. 1, the CPU 117 executes the processes by the program stored in the ROM in the memory group 108 and transfers the image data from the flash memory in the memory group 108 to the image compression/expansion unit 115.

The image processing apparatus 309 is realized by programs which are executed by the image compression/expansion unit 115, resolution converting unit 114, CPU 117, and memory group 108. Such an image processing method will be described hereinlater with reference to Figs. 10 to 12.

Fig. 10 is a block diagram showing a constructional example of the image processing apparatus 309.

The embodiment intends to reduce the image size by

5
10

15

20

25

switch 1002 and the compression ratio are set into the compression/expansion units 1004 and 1005 so as to use the Wavelet compression of a high compression ratio, for example, 1/100.

5 Reference numeral 1004 denotes the JPEG compression/expansion unit comprising a compressing/expanding circuit and an image buffer for work.

10 Reference numeral 1005 denotes the Wavelet compression/expansion unit comprising a compressing/expanding circuit and an image buffer for work.

15 Reference numeral 1006 denotes an image memory in which an image of a small size as a result of processing is written.

 The fourth embodiment will now be described with reference to Fig. 11.

20 The embodiment relates to another constructional example of the image processing apparatus 309 in Fig. 9. The image size is reduced by decreasing resolution (the number of constructing dots) of the image selected by the image selecting unit 304 in Fig. 9. For example, ordinarily, the object is photographed by resolution of (640 × 480) and the photographed image data is recorded into the image memory. When the
25 remaining amount of the image memory is small, the pixels of the image of (640 × 480) are thinned out to

09069419-042998

In Fig. 11, reference numeral 1101 denotes an image which is selected by the image selecting unit 304 and is processed.

10 Reference numeral 1103 denotes an image memory in
which the image of the small size as a processing
result is written.

The fifth embodiment will now be described with
20 reference to Fig. 12.

The embodiment relates to further another constructional example of the image processing apparatus 309. The image size is reduced by decreasing the number of bits constructing the image selected by the image selecting unit 304. For example, usually, color is constructed by the bit number of 24 bits and, when the remaining amount of the image memory is small,

In Fig. 12, reference numeral 1201 denotes the image which is selected by the image selecting unit 304 and is processed.

Reference numeral 1203 denotes an image memory in which an image of a small size as a processing result is written.

25 The method of saving the number of colors is realized not only by the operation by RGB but also by using YUV data. In this case, since the human being is

more sensitive to luminance than to the color difference, it is sufficient to remarkably reduce the number of bits of the color difference signal.

5 The features of the embodiments of the digital camera described above will now be summarized as follows.

886240" 6T469060
10 (1) When the remaining amount of the image memory is smaller than the predetermined amount, the image data is automatically selected by using the memory management information of the image memory such as recording date/time, final accessing date/time, accessing frequency, and the like, the image data is moved to another image server or the like by
15 communication, and an image memory necessary for new photographing is reserved.

(2) There is a feature that the remaining amount of the image memory is detected by using a plurality of threshold values in accordance with the photograph mode which is used by the photographer. That is, when the
20 user intends to record an image of high precision which needs a large amount of memory, many images are communicated. When the user wants to record an image of low resolution which needs only a small amount of memory, the photographer can photograph by
25 communicating a small amount of images.

(3) When the photographer photographs or just after he photographed, the communication image is selected by

using the marking information of the image inputted by the photographer. This method is a control method using a principle such that, ordinarily, when the photographer takes a picture, he has already grasped by
5 feeling whether the photographed image is a good picture or not.

(4) By performing image processes to the image which was automatically selected by a method similar to that mentioned in the above item (1), namely, by
10 executing the change of the compressing method by expanding the original image and recompressing it, the change of the compression parameters, the reduction of the number of constructing bits of the pixel also including the binarization, the reduction of the
15 resolution by resampling, or the like, the compression ratio of the recorded image is raised and a memory necessary for recording a new image is reserved without erasing the original images.

The contents of the above items (1) and (4) are
20 not contradictory. For example, in case of using wireless means such as PHS or the like as communicating means, the data cannot be always communicated. Therefore, by combining the control procedures of (1) and (4) and executing the image processes such as
25 recompression and the like when the transfer fails, the invention can cope with the use under a variety of environments.

006949-04998
366240-67469060

According to the embodiment, therefore, the foregoing problems of the memory capacity which is limited in the ordinary digital camera can be solved by transmitting the image or reducing the image size by
5 executing the image processes. Even at a photographing spot, the user can quickly photograph without losing a shutter chance.

Since the above control is realized by the transmission and process of the image or by the control
10 of the CPU, memory, or the like, a construction is simple. Such a control can be realized even in a digital camera with a transmitting apparatus or a digital camera with a work memory. Therefore, the realization of miniaturization of the digital camera,
15 low electric power consumption, and low costs is not obstructed. It can be said that the invention will be useful in future.

Particularly, the operation to erase the photographed image at the photographing spot
20 psychologically forces a burden on the photographer. Although a resistance feeling of the user to such a work is strong, it can be avoided by the transmission and the artificial deterioration of the image, so that there is a large advantage such that even an
25 unnecessary or defective image can be reserved any way.

A photographing apparatus such that the apparatus itself automatically transmits the image signal stored

09065419-042999

5 (Other embodiments of the Invention)

A construction such that to realize the function of the embodiment mentioned above, program codes of software to realize the function of the embodiment are supplied to an apparatus connected to various devices or a computer in a system so as to make the various devices operative, and the various devices are operated in accordance with programs stored in the computer (CPU or MPU) of the system or apparatus, thereby embodying the invention is also included in the scope of the invention.

In this case, the program codes themselves of the software realize the function of the embodiment mentioned above. The program codes themselves and means for supplying the program codes to the computer, for example, a storing medium in which the program codes have been stored construct the invention. As a storing medium to store the program codes, for example, any one of a floppy disk, a hard disk, an optical disk, a magnetooptic disk, a CD-ROM, a magnetic tape, a non-

volatile memory card, an ROM, and the like can be used.

In not only a case where the function of the foregoing embodiment is realized by executing the supplied program codes by the computer but also a case
5 where the function of the foregoing embodiment is realized in cooperation with the OS (Operating System) by which the program codes are operating by the computer or another application software or the like, the program codes are obviously included in the
10 embodiment of the invention.

Further, a case where after the supplied program codes were stored in a memory provided for a function expanding board of the computer or a function expanding unit connected to the computer, the CPU or the like
15 equipped to the function expanding board or the function expanding unit executes a part or all of the actual processes on the basis of an instruction of the program codes, and the function of the foregoing embodiment is realized by the process is also obviously
20 included in the invention.

As described above, according to the portable electronic apparatus and image processing method of the embodiment, a memory capacity of the image memory can be substantially increased while reserving the
25 photographed image, the number of images which can be photographed by the camera can be sufficiently increased without using the flash memory card, smart

0905449-042998

memory, or the other memories of a large capacity as in the conventional apparatus, accordingly, without enlarging the size of camera.

According to the recording medium in which the
5 programs have been recorded in the embodiment, the process for substantially increasing the memory capacity of the image memory while reserving the photographed images can be executed by the computer.

According to the photographing apparatus of the
10 embodiment, when the remaining amount of the image memory is small, the image according to a predetermined condition is selected from the images stored in the image memory and is transmitted to the outside or is subjected to proper processes and can be restored.
15 Thus, the memory capacity of the image memory can be substantially increased while reserving the photographed images. The number of images which can be photographed by the camera can be sufficiently increased without using the flash memory card, smart
20 memory, or the other memories of a large capacity as in the conventional apparatus, accordingly, without enlarging the size of camera.

According to the embodiment, in case of selecting, transmitting, and processing an image, a condition such
25 that the photographing date is old, the accessing frequency is small, the number of colors is small or large, or the like is used as a selecting condition,

09064419.042998
866240" 6T469060

thereby making it possible to transmit and process only an image of a small application field or an unnecessary image obtained due to a defective photographing or the like.

5 According to the embodiment, by adding the marking to the photographed image and setting such a marked image to the selecting condition, the priority to execute the transmission or process can be allocated to the photographed images.

10 According to the embodiment, when the photograph mode is changed, the process for selecting the image is performed in accordance with the image size in the photograph mode, therefore, even if there is a mode change, the image memory can be certainly reserved.

15 According to the embodiment, since the process for the image is executed when there is a photographing instruction, the image memory is certainly reserved when the shutter is depressed, and the photographed image can be certainly held.

20 After the selected image was transmitted or processed, the image is erased from the image memory and an empty space in the memory can be obtained.

 Since the selected image or the like is transmitted in a wireless manner, the image can be
25 preserved by a memory or the like of an apparatus on the reception side.

 By providing the communicating means of the

09069419 042998 866240 67469060

cellular phone, the selected image can be easily transmitted through the telephone line.

By providing each means such as microphone, speaker, audio process, or the like, the photographing apparatus can be also used as a cellular phone.

By dividing the photographing apparatus into two blocks, mutually rotatably coupling those blocks, providing the microphone for the first block, and providing the speaker for the other block, the photographing apparatus can be used in the most suitable form when it is used as a cellular phone.

By providing the image pickup means for one block and providing the display means for the other block, for instance, the photographer can be also photographed while displaying a self portrait of the photographer by rotating the block.

When the selected image is processed, it is compressed or the resolution is reduced or the number of colors is decreased and, after that, the resultant image data is stored into the image memory, thereby preserving the image in a state where the picture quality is slightly deteriorated, so that an empty space in the memory can be assured.

According to the recording medium on which the programs have been recorded, when the remaining amount of the image memory of the camera decreases, the processes such that the image according to the

09069419 042998
866240" 6TH9060

predetermined condition is selected from the images stored in the image memory and is transmitted to the outside or is subjected to a proper process and is restored can be executed by the computer built in the camera, so that the number of images which can be photographed by the camera can be increased.

Further, when the process to detect the remaining amount of the image memory of the camera in accordance with the setting of the photograph modes of the different image sizes is executed by the computer built in the camera, the necessary data can be obtained.

09069419.042998